

# CROSSOVER<sup>®</sup>

*In a class by itself.*

*The world's first small chassis stacked washer & dryer combo engineered to commercial laundry standards for your business needs.*



## PROFESSIONAL SPECIFICATIONS

Serving the Route and OPL laundry markets, Crossover Series stacked washer/dryer meet business demands with durability, energy savings and customer satisfaction.

## FEATURES AND BENEFITS

- ✓ 15,000+ cycle machine life design
- ✓ Large high security coin vault
- ✓ 4 professional wash programs, + 2 cycle options
- ✓ Field adjustable water levels + cycle
- ✓ Top quality SKF bearings in heavy duty assembly
- ✓ 3 seals (with 5 lips) protect bearings
- ✓ AC motor (no brushes)
- ✓ Professional 8-point suspension & Pump Drain Standard
- ✓ Solid steel counterweights—no concrete
- ✓ Commercial grade construction
- ✓ 22+ lb capacity and 7.5 cu ft drum
- ✓ Stainless steel fixed lint screen and roller supported tumbler
- ✓ Tapered sealed ribs bring load forward improving dryer performance

## BEST CUSTOMER EXPERIENCE

- ✓ Superior oversuds and unbalance tolerance
- ✓ Extra large door opening for easy loading and unloading
- ✓ Heavy-duty door hinge
- ✓ High speed 300G maximum extraction
- ✓ Simple, easy to use operation
- ✓ Axial airflow ensures the shortest drying time
- ✓ Easy clean lint screen
- ✓ Large capacity tumbler can handle oversized loads

## MARKET READY DESIGN

- ✓ Space-saving 27" wide to minimize floor space
- ✓ Quiet operation
- ✓ Liquid chemicals are fully diluted with water

NON-METERED STACKING WASHER AND  
DRYER—(GAS HEAT DRYER)  
Model No. WDSGNM

NON-METERED STACKING WASHER AND  
DRYER—ELECTRIC Model No. WDSENM

# Laundrylux<sup>®</sup>

866.580.1010 ✓ [laundrylux.com](http://laundrylux.com)



CEE TIER III  
COMPLIANT

# CROSSOVER STACKED WASHER/DRYER

## CROSSOVER STACK WASHER/DRYER SPECIFICATIONS

<b>Model No.</b>	DAWFS2GM - Gas
<b>Model No.</b>	DAWFS2EM - Electric
<b>Motor</b>	1/3 HP
<b>Electrical Rating (Gas Model)</b>	120VAC/60Hz/2W/1-phase
<b>Electrical Rating (Electric Model)</b>	208-240V/ 60Hz/1-phase
<b>Breaker/Fuse Requirements (Gas)</b>	15A
<b>Breaker/Fuse Requirements (Electric)</b>	30A
<b>Cylinder Volume</b>	7.5 cu ft/ 212.4 liters
<b>Cylinder Diameter</b>	25 3/4 in
<b>Cylinder Depth</b>	24 in
<b>Capacity (Dry Weight)</b>	10Kg/22lbs
<b>Door Opening</b>	17 1/4 in (438 mm)
<b>Airflow (Gas &amp; Electric)</b>	220 cfm
<b>Electric Heating (240VAC)</b>	5.4 kW
<b>Gas Heating</b>	26,000 Btu/hr (6,550 kcal/hr)
<b>Gas Connection</b>	3/8 in MNPT
<b>Tumbling Speed</b>	50 rpm
<b>Exhaust Connection</b>	4in Dia.
<b>Overall Dimensions</b>	W D H: 27 1/8 x 31 3/4 x 77 1/2 in
<b>Overall Dimensions</b>	W D H: 686 x 807 x 1968 mm
<b>Approximate Net Weight</b>	151 lbs

\*NOTE: the correct measurement of extraction efficiency is G-force, not RPM. A higher RPM does not mean greater extraction, which depends on cylinder diameter.



Refer installation and servicing to qualified, licensed personnel. Always read installation and Operating Manuals and consult local codes before installation. Protect machines with properly rated circuit breakers ONLY. Warranty void if not properly installed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.

*Laundrylux offers a complete line of Electrolux Professional and Wascomat Commercial Laundry equipment.*

# Laundrylux®

**866.580.1010 ✓ laundrylux.com**

Laundrylux • 461 Doughty Blvd., Inwood, NY 11096

Sales and Administration Tel: 516-371-4400 • Fax: 516-371-4204 • sales@laundrylux.com

Spare Parts Tel: 516-371-2000 • Fax: 516-371-4029 • parts@laundrylux.com

Technical Support – Tel: 516-371-0700 • Fax: 516-371-4029 • service@laundrylux.com

En Mexico: Llame gratis a este numero 001-800-010-1010